

# City Amberprint<sup>™</sup> Questionnaire





Project funded by the European Commission as part of the EU Framework Programme for Research and Innovation

Copyright © 2015 De Montfort University. All rights reserved.

# Introduction

City Amberprint<sup>™</sup> is a complement to the City Blueprint and the Trends and Pressures Framework.

The main goal of the City Amberprint<sup>™</sup> is a baseline assessment of the sustainability of Energy, Transport and ICT in cities. To comply with City Blueprint indicators that have a score between 0 (there is a concern) to 10 (no concern) are proposed. The quantitative indicators were "normalise" on a scale of 0 to 10, where 10 points were assigned to cities that met or exceeded certain criteria on environmental performance.

The structure is similar to the City Blueprint.

# Authors:

## Anna Strzelecka

anna.strzelecka@dmu.ac.uk Water Software Systems (WSS) School of Engineering and Sustainable Development (SESD) De Montfort University 00.26 Hawthorn Building The Gateway Leicester LE1 9BH United Kingdom

## Prof. Bogumil Ulanicki

bul@dmu.ac.uk
Head of Centre for Engineering Science and Advanced Systems (CESAS)
Director of Research, Water Software Systems (WSS)
School of Engineering and Sustainable Development (SESD)
De Montfort University
Gateway House (GH6.60)
The Gateway
Leicester LE1 9BH
United Kingdom

# 1 Energy Indicators

## 1.1 Indicator 1 - CARBON FOOTPRINT

Principal: How does your carbon footprint (CF) per person compare with the international range? A lower indicator score is given for a larger carbon footprint.

How to calculate:

The CF value for your city is standardized with the average of the upper and lower 10% of available data.

Average minimum CF in 2012 was 0.237 (tonnes CO<sub>2</sub>/capita/year).

Average maximum CF in 2012 was 16.464 (tonnes CO<sub>2</sub>/capita/year).

Where the CF/capita value for your city is **X**, the indicator is calculated as follows:

 $\mbox{Indicator 1} \ = 10 \times \frac{16.464 - X}{16.464 - 0.237}$ 

**Definition of Carbon Footprint**: the total sets of greenhouse gas emissions caused by an organization, event, product or person.

**Example.** For Anycity the CF value is 5.161 tonnes/cap/year (2013). Therefore:

Indicator 1 = 
$$10 \times \frac{16.464 - 5.161}{16.464 - 0.237} = 6.9$$

Where to get the data:

For the UK:

https://www.gov.uk/government/statistics/uk-local-authority-and-regional-carbondioxide-emissions-national-statistics-2005-2013

https://data.oecd.org/air/air-and-ghg-emissions.htm

## Indicator 1 evaluation

Description	Units	Value	Code in formula
Carbon Footprint/capita	tCO <sub>2</sub> /cap/yr		x
Formula		$10\times \frac{16.464-X}{16.464-0.237}$	
Result			

## Indicator 1 - CARBON FOOTPRINT – direct links

Water	Energy is used to pump clean water and wastewater; energy can be gen- erated from wastewater or from clean water (turbines)
Waste	Waste disposal contributes to $CO_2$ emissions (e.g. landfill sites), reuse and recycling can reduce $CO_2$ emissions
Energy	
Transport	Transport generates $CO_2$ (e.g. from combustion engines)
ІСТ	ICT can improve efficiency of many processes/plants which generate $CO_2$ (e.g. by more energy efficient operation)

## 1.2 Indicator 2 - FUEL POVERTY

Principal: What is the proportion of households in the city that are considered to be fuel poor? The lower indicator score is given when the proportion is higher.

#### How to calculate:

Under the Low Income High Costs definition, a household is considered to be fuel poor if:

- they have required fuel costs that are above average (the national median level)
- were they to spend that amount, they would be left with a residual income below the official poverty line.

The indicator is calculated as the percentage of households in the city that is considered to be fuel poor X divided by 10.

Therefore:

Indicator 2 = (100 - X)/10

**Example.** For Anycity the percentage of households which is considered to be fuel poor is 16.6% (in 2013). Therefore:

Indicator 2 = (100 - 16.6)/10 = 8.3

Where to get the data:

Data for cities needs to be researched locally.

For the UK:

```
https://www.gov.uk/government/statistics/2013-sub-regional-fuel-poverty-data-low-income-high-costs-indicator
```

#### Indicator 2 evaluation

Description	Units	Value	Code in formula
% of fuel poor households	%		x
Formula		$(100-\mathbf{X})/10$	
Result			

## Indicator 2 - FUEL POVERTY – direct links

Water	no direct links identified
Waste	can be considered as fuel
Energy	
Transport	no direct links identified
ІСТ	can alleviate the fuel poverty by efficient use of energy

## 1.3 Indicator 3 - ENERGY CONSUMPTION

Principal: This indicator presents how does total energy consumption (domestic, industrial and commercial, and transport) per capita in the city compares with the international range. A lower indicator score is given where the consumption is greater.

#### How to calculate:

The total energy consumption in the city (kgoe/cap/yr) is placed between the highest and the lowest energy consumption per capita per year.

Energy consumption includes: coal (includes coal consumed in all the following sectors: Heat Generation, Energy Industry use, Industry, Public administration, Commercial, Agriculture, Miscellaneous); manufactured fuels (includes only manufactured solid fuels and not derived gases); Petroleum products (includes petroleum consumed in all the following sectors: Heat Generation, Energy Industry use, Industry, Public administration, Commercial, Agriculture, Miscellaneous); gas; electricity; bioenergy & wastes.

The lowest average energy consumption per capita is: 893.15 kgoe/cap/yr (in 2012).

The highest average energy consumption per capita is: 5419.0 kgoe/cap/yr (in 2012).

The indicator is calculated as follows (where X is the total energy consumption for city that is under consideration):

Indicator  $3 = 10 \times \frac{5419 - X}{5419 - 893.15}$ 

**Example.** For Anycity the total energy consumption was 1540.9 kgoe/cap/yr (in 2012). Therefore:

Indicator  $3 = 10 \times \frac{5419 - 1540.9}{5419 - 893.15} = 8.6$ 

Where to get the data:

http://ec.europa.eu/eurostat/tgm/table.do?tab=table&init=1&language=en&pcode=ten00095&
plugin=1

https://www.gov.uk/government/statistical-data-sets/total-final-energy-consumptionat-regional-and-local-authority-level-2005-to-2010

For the cities data needs to be researched locally.

#### Indicator 3 evaluation

Description	Units	Value	Code in formula
Energy consumption	kgoe/cap/yr		x
Formula		$10\times \frac{5419-X}{5419-893.15}$	
Result			

Water	Water usage contributes to energy consumption
Waste	The quantity of waste produced affects the energy consumption of the waste treatment and disposal process
Energy	
Transport	Transport contributes to energy consumption
ICT	ICT can improve efficiency of many processes/plants (e.g. smart building technologies built on ICT systems can make building design, construction and operation more energy efficient)

#### Indicator 3 - ENERGY CONSUMPTION – direct links

## 1.4 Indicator 4 - ENERGY SELF-SUFFICIENCY

<u>Principal:</u> Measure of the proportion of a city's demand that could be met through indigenous production including renewable resources, waste, and traditional but generated locally in the city. A lower indicator score is given where self-sufficiency is lower.

#### How to calculate:

A city is energy self-sufficient if it is able to produce energy locally, e.g. from renewable sources, waste, or using fossil fuels. It shows how resilient city is in case of a sudden loss of connection with the power grid. The indicator is calculated as the amount of energy generated locally X to the total energy consumption in the city Y.

Indicator  $4 = 100 \times X/Y$ 

**Example.** For Anycity the total energy consumption was 1540.9 kgoe/cap/yr (in 2012). The amount of energy generated locally was 99 kgoe/cap/yr (in 2012) Therefore:

Indicator  $4 = 10 \times 99/1540.9 = 0.64$ 

Where to get the data:

https://www.gov.uk/government/statistics/energy-trends-december-2014

#### Indicator 4 evaluation

Description	Units	Value	Code
			in formula
The amount of energy generated locally	_		x
Total energy consumption in the city	-		Y
Formula		$10  imes \mathbf{X} / \mathbf{Y}$	
Result			]

## Indicator 4 - ENERGY SELF-SUFFICIENCY – direct links

Water	Energy is used to pump clean water and wastewater; energy can be generated from wastewater or from clean water (turbines)
Waste	Some of the energy demand could be obtained from waste incinera- tion. Organic waste and bio-masses can be seen as a renewable source of bio-gas (for instance, when added to sludge in the process of co- digestion)
Energy	
Transport	Hybrid vehicles are capable of producing part of the energy they use for motion
ІСТ	no direct links identified

## 1.5 Indicator 5 - RENEWABLE ENERGY RATIO

Principal: A measure of proportion of total energy derived from renewable sources in the city, as a share of the city's total energy consumption compared to the international range. A lower indicator is given where the percentage is lower.

#### How to calculate:

The share of a city's total energy consumption derived from renewable sources is calculated as the percentage of total energy derived from renewable sources **X** and compared to the international range. Consumption of renewable sources should include geothermal, solar, wind, hydro, tide and wave energy, and combustibles, such as biomass.

The lowest average percentage of energy derived from renewable sources is: 1.15% (in 2012).

The highest average percentage of energy derived from renewable sources is: 98.8% (in 2012).

The indicator is calculated as follows (where X is the percentage of energy derived from renewable sources):

 $Indicator \ 5 = 10 \times \frac{X - 1.15}{98.8 - 1.15}$ 

**Example.** For the UK the percentage of total energy derived from renewable sources was 13.9% in 2013. Therefore:

Indicator 
$$5 = 10 \times \frac{13.9 - 1.15}{98.8 - 1.15} = 1.31$$

Where to get the data:

http://www.eia.gov/beta/international/

http://ec.europa.eu/eurostat/web/energy/data/main-tables

## Indicator 5 evaluation

Description	Units	Value	Code in formula
Energy derived from renewable sources as % of total consumption	%		х
Formula		$10 imes {X-1.15\over 98.8-1.15}$	
Result			

Water	no direct links identified
Waste	Some of the energy demand could be obtained from waste (e.g. sludge can be used to produce energy)
Energy	
Transport	no direct links identified
ІСТ	no direct links identified

#### Indicator 5 - RENEWABLE ENERGY RATIO – direct links

## 1.6 Indicator 6 - ENERGY EFFICIENCY PLANS

Principal: Measure of the application of energy efficiency measures by the range of energy users across the city. A lower indicator score is given where efficiency measures are more limited.

#### How to calculate:

This measure is unlikely to already have a value applied. Instead, apply a self assessment based on information from public sources (national/regional/local policy document, reports and websites of actors (e.g. energy companies, cities, provincial or national authorities). It should consider plans, measures and their implementation to improve the efficiency of energy usage

- at household level, e.g. efficient household appliances,
- at community level by energy efficient buildings or energy recycling, e.g. heat can be collected in summer, and stored to use it in winter,
- by encouraging people to change their behaviour.

Indicator score	Assessment
0	no information is available on this subject
1	limited information is available in a national document
2	limited information is available in national and local documents
3	the topic is addressed in a chapter in a national document
4	the topic is addressed in a chapter at the national and local level
5	a local policy plan is provided in a publicly available document
6	as 5 and the topic is also addressed at the local website
7	plans are implemented and clearly communicated to the public
8	as 7 plus subsidies are made available to implement the plans
9	as 8 plus annual reports are provided on the progress of the implementation and/or any other activity indicating that this is a very high priority imple- mented at the level of the local community
10	as 9 and the activity is in place for = 3 years

The following guidance is proposed to make self-assessment score for Indicator 6.

**Example.** In Anycity plans for energy conservation are clearly communicated to public via website. There is a scheme to install smart meters in the houses by 2020. Therefore Anycity is given a score of 6.

#### Where to get the data:

Data needs to be researched locally.

#### **Indicator 6 evaluation**

Description	Value
Energy efficiency	

## Indicator 6 - ENERGY EFFICIENCY ACTION PLANS – direct links

Water	Water efficient appliances can contribute to efficient energy use
Waste	Some of the energy demand could be obtained from waste (e.g. waste incineration)
Energy	
Transport	Energy efficient means of public and private transportation (bio-gas pow- ered bus and coaches, high efficient car engines, hybrid vehicles, etc.)
ІСТ	ICT can improve efficiency of many processes/plants (e.g. through run- ning heating or cooling according to each occupant's needs)

## 1.7 Indicator 7 - ENERGY INFRASTRUCTURE INVESTMENT

Principal: A measure of the investment in the infrastructure for energy distribution compared to the international range. A lower indicator score is given where the investment is lower.

How to calculate:

The infrastructure investment is an indication of the commitment to regularly invest in the energy infrastructure. Investment can be in:

- a new infrastructure
- maintaining
- and refurbishing the existing one.

The investment in the city/region by capita, X is calculated as the investment in the city/region A in a year (values of the investment over the last 5 years should be taken and average value per year used) divided by local population of the city/region B:

$$\mathbf{X} = \mathbf{A}/\mathbf{B}$$

Subsequently, the investment in the city/region per capita X is divided by GDP per capita in the country Y.

The average lowest percentage of investment is 0.06%.

The average highest percentage of investment is 2.29%.

Therefore, the indicator is calculated as follows:

$${
m Indicator} \,\, 7 = rac{100 imes {
m X} / {
m Y} - 0.06}{2.29 - 0.06} imes 10$$

**Example:** In Anycity £657 million was invested in the energy infrastructure (in the last 5 years; on average per year it is £131.4 million). Population in the area is 4.533 million. Therefore the investment per capita X is:

$$X = 131.4/4.533 = 28.99 [\pounds/cap]$$

GDP per capita in the UK is £30074.59 [£/cap]. Therefore:

Indicator 7 = 
$$\frac{100 \times 28.99/30074.59 - 0.06}{2.29 - 0.06} \times 10 = 0.17$$

Where to get the data:

Data for cities needs to be researched locally

Data for countries:

http://data.worldbank.org/indicator/IE.PPI.ENGY.CD

## Indicator 7 evaluation

Description	Units	Value	Code in formula
Investment in the energy infrastructure per capita (in the city/region)	£(€)/cap		x
GDP per capita (in the country)	£(€)/cap		Y
Formula		$\frac{100\times \mathrm{X/Y}-0.06}{2.29-0.06}\times 10$	
Result			

#### Indicator 7 - ENERGY INFRASTRUCTURE INVESTMENT – direct links

Water	Investment in the energy infrastructure can prompt water utilities to carry out the necessary work (e.g. replacing old pipes, or installing new ones)
Waste	no direct links identified
Energy	
Transport	Road works associated with investment in the energy infrastructure may disturb transport
ІСТ	Investment in the energy infrastructure can prompt ICT companies to carry out the necessary work

# 2 Transport Indicators

## 2.1 Indicator 8 - COMMUTING TIME

<u>Principal:</u> A measure of the proportion of time spent on commuting (minutes per day). Includes average time spent in: public transport (bus, coach, train, underground, tram, light railway), car (as driver or passenger), motorcycle, moped, scooter, bicycle, taxi on the way to and from work. A lower indicator score is given where the time spent on commuting is greater.

<u>How to calculate:</u> Commuting time is calculated as average time spent on commuting in one day (in minutes) compared to the international range.

The average minimum time spent on commuting is 10.8 min/day.

The average maximum time spent on commuting is 74.2 min/day.

The indicator is calculated as follows (where **X** is the average time spent on commuting in the city (or region)):

 $Indicator \ 8 = 10 \times \frac{74.2 - X}{74.2 - 10.8}$ 

**Example.** For Anycity an average time spent on commuting each day is 48.75 minutes (in 2013). Therefore:

Indicator 
$$8 = 10 \times \frac{74.2 - 48.75}{74.2 - 10.8} = 6$$

Where to get the data:

https://www.tuc.org.uk/

http://ec.europa.eu/eurostat/web/products-datasets/-/lfst\_r\_lfe2ecomm

http://www.nationmaster.com/country-info/stats/Transport/Commute/Time-spent

Data for the cities needs to be researched locally.

Description	Units	Value	Code in formula
Average time spent on commuting	min/day		х
Formula		$10 imesrac{74.2- ext{X}}{74.2-10.8}$	
Result			

#### **Indicator 8 evaluation**

#### Indicator 8 - COMMUTING TIME – direct links

Water	no direct links identified
Waste	no direct links identified
Energy	Availability of energy can affect the commuting time
Transport	
ІСТ	ICT can improve efficiency of managing transport in the city reducing commuting time

## 2.2 Indicator 9 - PUBLIC TRANSPORT USE

Principal: Kilometres travelled by public transport and bicycles compared to overall kilometres travel by all means of transport. A lower indicator score is given where the use of public transport and bicycles is higher.

#### How to calculate:

Average kilometres travelled by public transport and bicycles **X** divided by overall kilometres travelled by all means of transport *Y*.

Indicator  $9 = 10 \times (X/Y)$ 

**Example.** In Anycity in 2013 overall traffic was 399,844 (thousand vehicle miles) compared to 2,816 (cyclists, pedestrians) and 4,776 public transport (thousand vehicle miles). Therefore:

Indicator  $9 = 10 \times (7, 592/399, 844) = 0.18$ 

Where to get the data:

Data needs to be researched locally.

#### **Indicator 9 evaluation**

Description	Units	Value	Code in formula
Km travelled by public transport & cycling	km		x
Km travelled by all means of transport	km		Y
Formula		$10\times (X/Y)$	
Result			

#### Indicator 9 - PUBLIC TRANSPORT USE - direct links

Water	Can be used as infrastructure for transportation
Waste	Can be used as a fuel for public transport
Energy	is required for transportation
Transport	
ICT	ICT can improve efficiency of managing transport in the city

## 2.3 Indicator 10 - BICYCLE NETWORK

Principal: Length of bicycle network per inhabitant compared to the international range. The lower indicator score is given where the length of bicycle network per inhabitant is lower.

### How to calculate:

It includes networks removed from the road, marked and signed only along street and roads, physically separated along streets and roads.

Total length of bicycle network in meters A divided by number of inhabitants B.

 $\mathbf{X} = \mathbf{A}/\mathbf{B}$ 

This data already exist for some cities. Total length of bicycle network per capita will be compared with Amsterdam, where there is 2.03 metres of bicycle network per capita (and the shortest is 0 metres per capita). Therefore:

Indicator  $10 = 10 \times (X/2.03)$ 

**Example.** Length of designated cycle routes in metres per inhabitant in Anycity in 2013 was 0.44. Therefore:

Indicator  $10 = 10 \times (0.44/2.03) = 2.2$ 

Where to get the data:

Data needs to be researched locally.

### Indicator 10 evaluation

Description	Units	Value	Code in formula
Length of designated cycle routes	m		Α
Number of inhabitants	No.		В
Total length of bicycle network in meters $\mathbf{X} = \mathbf{A}/\mathbf{B}$	m/cap		х
Formula		$10  imes (\mathbf{X}/2.03)$	
Result			

## Indicator 10 - BICYCLE NETWORK – direct links

Water	good bicycle paths are often along canals
Waste	no direct links identified
Energy	no direct links identified
Transport	
ІСТ	no direct links identified

## 2.4 Indicator 11 - TRANSPORTATION FATALITIES

Principal: A measure of transportation fatalities per year. A lower indicator score is given where the number is greater.

## How to calculate:

Transportation fatalities per 100 000 population is calculated as the number of fatalities related to transportation of any kind within the city borders X, divided by 100,000 of the city's total population Y. The result is expressed as the number of transportation fatalities per 100 000 population and compared to the international range. The city shall include in this indicator deaths due to any transportation-related proximate causes in any mode of travel (automobile, public transport, walking, bicycling, etc.). The city shall count any death directly related to a transportation incident within city limits, even if death does not occur at the site of the incident, but is directly attributable to the accident.

The lowest average transport fatalities per 100 000 population is 3.6 (in 2013).

The highest average transport fatalities per 100 000 population is 33.4 (in 2013).

 $Indicator \ 11 = 10 \times \frac{33.4 - X/Y}{33.4 - 3.6}$ 

**Example.** In Anycity in 2013 there were 24 killed in traffic accidents. The population of Anycity is 329,839. Therefore:

Indicator 
$$11 = 10 \times \frac{33.4 - (24/329, 839) * 100000}{33.4 - 3.6} = 8.8$$

Where to get the data:

Data needs to be researched locally.

Global Status Report on Road Safety 2013: supporting a decade of action. WHO

Description	Units	Value	Code in formula
Number of transportation fatalities	-		x
Number of inhabitants	-		Y
Formula		$10 imes {{33.4 - { m X}/{ m Y}}\over{ m 33.4 - 3.6}}$	
Result			

## Indicator 11 evaluation

## Indicator 11 - TRANSPORTATION FATALITIES – direct links

Water	no direct links identified
Waste	no direct links identified
Energy	no direct links identified
Transport	
ІСТ	ICT can improve efficiency of managing transport in the city

## 2.5 Indicator 12 - CLEAN ENERGY TRANSPORT

Principal: Clean energy transport and clean energy sharing transport. A lower indicator score is given where efficiency measures are more limited.

#### How to calculate:

This measure is unlikely to already have a value applied. Instead, apply a self assessment based on information from public sources (national/regional/local policy document, reports and websites of actors (e.g. transport companies, cities, provincial or national authorities). It should consider plans, measures and their implementation to improve the transport efficiency by e.g.

- efficient public transport (electric train, subway/metro, tram, cable railway)
- efficient private transport (electric taxis or cars, electric scooter, bicycling)
- and encouragements to use public transport.

Indicator score	Assessment
0	no information is available on this subject
1	limited information is available in a national document
2	limited information is available in national and local documents
3	the topic is addressed in a chapter in a national document
4	the topic is addressed in a chapter at the national and local level
5	a local policy plan is provided in a publicly available document
6	as 5 and the topic is also addressed at the local website
7	plans are implemented and clearly communicated to the public
8	as 7 plus subsidies are made available to implement the plans
9	as 8 plus annual reports are provided on the progress of the implementation and/or any other activity indicating that this is a very high priority imple- mented at the level of the local community
10	as 9 and the activity is in place for = 3 years

The following guidance is proposed to make self-assessment score for Indicator 12.

**Example.** In Anycity there is no bike sharing schemes. There is park and ride scheme and car sharing scheme. There is investment in cycling and cycle paths. There are 6 charging stations for electric cars. Therefore Anycity is given value 10.

#### Where to get the data:

Copyright © 2015 De Montfort University. All rights reserved.

Data needs to be researched locally.

## Indicator 12 evaluation

Description	Value	
Clean energy transport		

## Indicator 12 - CLEAN ENERGY TRANSPORT – direct links

Water	Clean transportation reduces water pollution and purification costs
Waste	no direct links identified
Energy	Clean energy means of transport reduce the exploitation of other energy sources
Transport	
ІСТ	ICT can help to plan to achieve higher level of efficiency of transport

## 2.6 Indicator 13 - TRANSPORT-RELATED POLLUTIONS

Principal: Air pollutant emissions (Carbon monoxide (CO), Nitrogen oxides (NO<sub>x</sub>), Particulates ( $PM_{10}$ ) - airbourne particulate matter with aerodynamic diameter less than 10 micrometres, Particulates ( $PM_{2.5}$ ) - airbourne particulate matter with aerodynamic diameter less than 2.5 micrometres, Benzene, 1,3-butadiene, Lead (Pb), Sulphur oxides ( $SO_x$ )) from transport. A lower indicator score is given where the pollutant emissions are greater.

### How to calculate:

Each of air pollutant will be compared with the international range. Therefore:

• Sulphur oxides (SO<sub>x</sub>):

The lowest average emissions is 0.114 kg/cap/yr.

The highest average emissions is 2.753 kg/cap/yr. Therefore:

$${
m SO}_{
m x}=rac{2.753-{
m A}}{2.753-0.114} imes 10$$

where A is the emissions from the city (kg/cap/yr).

• Nitrogen oxides (NO<sub>x</sub>):

The lowest average emissions is 4.095 kg/cap/yr.

The highest average emissions is 36.53 kg/cap/yr. Therefore:

$$NO_x = \frac{36.53 - B}{36.53 - 4.095} \times 10$$

where B is the emissions from the city (kg/cap/yr).

• Ammonia (NH<sub>3</sub>):

The lowest average emissions is 0.021 kg/cap/yr.

The highest average emissions is 0.337 kg/cap/yr. Therefore:

$${
m NH_3} = rac{0.337 - {
m C}}{0.337 - 0.021} imes 10$$

where C is the emissions from the city (kg/cap/yr).

• Non-methane volatile organic compounds:

The lowest average emissions is 0.432 kg/cap/yr.

The highest average emissions is 5.643 kg/cap/yr. Therefore:

$${
m Non-mth} = rac{5.643 - {
m D}}{5.643 - 0.432} imes 10$$

where D is the emissions from the city (kg/cap/yr).

• Particulates (PM<sub>10</sub>):

The lowest average emissions is 0.169 kg/cap/yr.

The highest average emissions is 2.197 kg/cap/yr. Therefore:

$$\mathbf{PM_{10}} = \frac{2.197 - \mathbf{E}}{2.197 - 0.169} \times 10$$

where E is the emissions from the city (kg/cap/yr).

The indicator is calculated as an average of all sub-indicators:

Indicator  $\mathbf{13} = (\mathbf{SO}_{\mathbf{x}} + \mathbf{NO}_{\mathbf{x}} + \mathbf{NH}_{\mathbf{3}} + \mathbf{Non}\mathbf{-mth} + \mathbf{PM}_{\mathbf{10}})/\mathbf{5}$ 

Example. For Anycity the sub-indicators are as follows:  $SO_x = 9.56$ ,  $NO_x = 9.29$ ,  $NH_3 = 7.12$ , Non-mth = 9.48,  $PM_{10} = 8.89$ . Therefore:

Indicator 13 = (9.56 + 9.29 + 9.48 + 7.33 + 8.89)/5 = 8.91

#### Where to get the data:

https://www.gov.uk/government/collections/energy-and-environment-statistics

http://www.eea.europa.eu/data-and-maps/indicators/transport-emissions-of-air-pollutants-8/transport-emissions-of-air-pollutants-9

http://ec.europa.eu/eurostat/web/environment/air-emissions-inventories/database

Description	Units	Value	Code in formula
Sulphur oxides emissions in the city	t		Α
${f SO}_{f x}=rac{2.753-{f A}}{2.753-0.114} imes 10$	_		$SO_x$
Nitrogen oxides emissions in the city	kg/cap/yr		В
${f NO_x} = rac{{36.53 - B}}{{36.53 - 4.095}}  imes 10$	_		NO <sub>x</sub>
Ammonia emissions in the city	kg/cap/yr		с
${f NH_3}=rac{0.337-{f C}}{0.337-0.021} imes 10$	_		$ m NH_3$
Non-methane volatile organic com- pounds emissions in the city	kg/cap/yr		D
${f Non-mth}=rac{{f 5.643}-{f D}}{{f 5.643}-{f 0.432}} imes {f 10}$	_		Non-mth
Particulates ( $PM_{10}$ ) emissions in the city	kg/cap/yr		E
${ m PM_{10}}=rac{2.197-{ m E}}{2.197-0.169} imes 10$	_		$PM_{10}$
Formula		$(SO_x + NO_x + NH_3 +$ Non-mth + PM <sub>10</sub> )/5	
Result			

#### Indicator 13 evaluation

Water	Pollutants from road surfaces contaminate drainage water	
Waste	no direct links identified	
Energy	no direct links identified	
Transport		
ІСТ	ICT can improve efficiency of managing transport in the city	

## 2.7 Indicator 14 - TRANSPORT INFRASTRUCTURE INVESTMENT

Principal: A measure of the investment in the transport infrastructure. A lower indicator score is given where the investment is lower.

How to calculate:

The infrastructure investment is an indication of the commitment to regularly invest in the transport infrastructure. Investment can be in:

- a new infrastructure
- maintaining
- and refurbishing the existing one.

The investment in the city/region by capita, **X** is calculated as the investment in the city/region **A** divided by local population of the city/region **B**:

 $\mathbf{X}=\mathbf{A}/\mathbf{B}$ 

Subsequently, the investment in the city/region per capita X is divided by GDP per capita in the country Y.

The average lowest percentage of investment is 0.02%.

The average highest percentage of investment is 3.89%.

Therefore, the indicator is calculated as follows:

 $\text{Indicator } 14 = \frac{100 \times \mathbf{X}/\mathbf{Y} - 0.02}{3.89 - 0.02} \times 10$ 

**Example:** In Anycity £319.20 million was invested in the transport infrastructure (in 2014/15). Population in the area is 4.533 million. Therefore the investment per capita **X** is:

 $X = 319.20/4.533 = 70[\pounds/cap]$ 

GDP per capita in the UK is £30074.59 [£/cap]. Therefore:

Indicator  $14 = \frac{100 \times 70/30074.59 - 0.06}{2.29 - 0.06} \times 10 = 0.78$ 

Comment: the principle is the same as indicator 7.

Where to get the data:

Data for cities needs to be researched locally.

Date for countries:

http://data.worldbank.org/indicator/IE.PPI.TRAN.CD

## Indicator 12 evaluation

Description	Units	Value	Code in formula
Investment in the transport infrastructure per capita (in the city/region)	£(€)/cap		x
GDP per capita (in the country)	£(€)/cap		Y
Formula		$\frac{100 \times {\rm X/Y} - 0.02}{3.89 - 0.02} \times 10$	
Result			

## Indicator 14 - TRANSPORT INFRASTRUCTURE INVESTMENT – direct links

Water	Investment in transport infrastructure, e.g. by refurbishing roads, may prompt water utilities to carry out necessary works
Waste	no direct links identified
Energy	Investment in transport infrastructure may prompt energy utilities to carry out necessary works
Transport	
ІСТ	Investment in transport infrastructure may prompt ICT companies to carry out necessary works

# 3 ICT Indicators

## 3.1 Indicator 15 - ICT ACCESS

Principal: The ICT access is a measure of access to information and communication technology (ICT) in the city. A lower indicator score is given where the ICT access is lower.

## How to calculate:

Following sub-indicators need to be calculated and an average value is taken.

• Mobile-cellular telephone subscriptions per 100 inhabitants, where **X** is the number of mobile-cellular telephone subscriptions per 100 inhabitants in the city:  $A = 10 \times X/120$ 

• International Internet bandwidth (bit/s) per Internet user, where Y is the International Internet bandwidth (bit/s) per Internet user in the city:  $B = 10 \times Y/787, 260$ 

- Proportion of households with a computer, where Z is the percentage of households with a computer in the city:  ${\bf C}={\bf Z}/10$ 

- Proportion of households with Internet access, where  ${\bf Q}$  is the percentage of households with Internet access in the city:  ${\bf D}={\bf Q}/10$ 

Therefore, the indicator is calculated as follows:

Indicator 15 = (A + B + C + D)/4

**Example.** For Anycity :

Number of mobile-cellular telephone subscriptions per 100 inhabitants: **X = 124**. Therefore:

 $A = 10 \times 124/120 = 10$ 

International Internet bandwidth (bit/s) per Internet user: Y = 352,583. Therefore:

 $\mathbf{B} = 10 \times 352, 583/787, 260 = 4.5$ 

Percentage of households with a computer: **Z = 88.2 %**. Therefore:

$$C = 88.2/10 = 8.8$$

Percentage of households with Internet access: Q = 84 %. Therefore:

$$\mathbf{D} = 84/10 = 8.4$$

The indicator is calculated as follows:

Indicator 15 = (10 + 4.5 + 8.8 + 8.4)/4 = 7.9

Where to get the data:

Data needs to be researched locally.

## Indicator 15 evaluation

Description		Value	Code in formula
Number of mobile-cellular telephone subscriptions per 100 inhabitants in the city	No.		X
Mobile-cellular telephone subscriptions per 100 inhabitants $\mathbf{A}=10\times\mathbf{X}/120$	_		Α
International Internet bandwidth per Internet user in the city	bit/s		Y
International Internet bandwidth per Internet user $\mathbf{B}=10\times\mathbf{Y}/787,260$			В
Percentage of households with a computer in the city	%		z
Proportion of households with a computer $\mathbf{C}=\mathbf{Z}/10$			С
Percentage of households with Internet access in the city	%		Q
Proportion of households with Internet access $\mathbf{D}=\mathbf{Q}/10$	_		D
Formula		$\frac{\mathbf{A} + \mathbf{B} + \mathbf{C} + \mathbf{D}}{4}$	
Result			

## Indicator 15 - ICT ACCESS – direct links

Water	People have more tools to get informed about water topics. It increases awareness
Waste	People have more tools to get informed about waste topics. It increases awareness
Energy	People have more tools to get informed about energy topics. It increases awareness
Transport	Access to information about public transport, traffic, available routes
ІСТ	

## 3.2 Indicator 16 - ICT USE HOUSEHOLD

Principal: The ICT use is a measure of use of information and communication technology (ICT) in the city. A lower indicator score is given where the ICT use is lower.

### How to calculate:

Following sub-indicators need to be calculated and an average value is taken.

• Proportion of individuals using the Internet, where **X** is the percentage of population in the city using the Internet: A = X/10

• Fixed (wired)-broadband subscriptions per 100 inhabitants, where **Y** is the number of fixed (wired)-broadband subscriptions per 100 inhabitants in the city:  $\mathbf{B} = \mathbf{10} \times \mathbf{Y}/\mathbf{60}$ 

• Wireless-broadband subscriptions per 100 inhabitants, where Z is the number of wireless-broadband subscriptions per 100 inhabitants in the city: C = Z/10

Therefore, the indicator is calculated as follows:

Indicator  $16 = (\mathbf{A} + \mathbf{B} + \mathbf{C})/3$ 

**Example.** For Anycity :

Percentage of individuals using the Internet: **X = 89.9**. Therefore:

$$\mathbf{A} = 89.9/10 = 9.0$$

Number of fixed (wired)-broadband subscriptions per 100 inhabitants: **Y = 37.8**. Therefore:

 $\mathbf{B} = 10 \times 37.8/60 = 6.3$ 

Number of wireless-broadband subscriptions per 100 inhabitants: **Z = 79.6**. Therefore:

C = 79.6/10 = 8.0

The indicator is calculated as follows:

Indicator 16 = (9 + 6.3 + 8)/3 = 7.7

Where to get the data:

Data needs to be researched locally.

## Indicator 16 evaluation

Description		Value	Code in formula
Percentage of population in the city using the Internet	%		X
Proportion of individuals using the Internet $\mathbf{A}=\mathbf{X}/10$	_		A
Number of fixed (wired)-broadband subscriptions per 100 inhabitants in the city	No.		Y
Fixed (wired)-broadband subscriptions per 100 inhabitants $\mathbf{B}=10\times\mathbf{Y}/60$	_		В
Number of wireless-broadband subscriptions per 100 in- habitants in the city	No.		Z
Wireless-broadband subscriptions per 100 inhabitants $\mathbf{C}=\mathbf{Z}/10$	_		С
Formula		$\frac{\mathbf{A} + \mathbf{B} + \mathbf{C}}{3}$	
Result			

## Indicator 16 - ICT USE HOUSEHOLDS – direct links

Water	People have more tools to get informed about water topics. It increases awareness
Waste	People have more tools to get informed about waste topics. It increases awareness
Energy	People have more tools to get informed about energy topics. It increases awareness
Transport	People have more tools to get informed about transport topics. It in- creases awareness
ІСТ	

## 3.3 Indicator 17 - ICT USE WATER UTILITIES

<u>Principal:</u> A measure of ICT implementation at the city utility level. A lower indicator score is given where there are less ICT tools implemented.

How to calculate:

Description	Score (0-10) evaluated locally	Comments
Operation		e.g. SCADA system, energy management
Maintenance		e.g. asset management data base and GIS
Dianning and design		
Planning and design		e.g. optimisation, GIS intenace
Customer service		e.g. smart metering

For Anycity :

- Smartphone app "Love Leicester" where people can report floods, leaks, etc.
- Flood warning system
- Flow gauges and rainfall gauges to collect data

• Engaging with communities in flood risk areas; flood wardens are chosen from the local community

- New buildings have meters for billing purposes
- Water management system within buildings to prevent leaks
- Leakage detection for district heating pipelines
- Leakage detection for pipelines

• SWIMS – Severe Weather Impacts Monitoring System. Each council service will log the impacts of, and its responses to, severe weather events onto the online data capture facility

Therefore in Anycity :

Description	Score (0-10)	Comments
	evaluated locally	
Operation	10	e.g. SCADA system, energy management
Maintenance	10	e.g. asset management data base and GIS
Planning and design	7	e.g. optimisation, GIS interface
Customer service	2	e.g. smart metering

Indicator 17 = (10 + 10 + 7 + 2)/4 = 7.3

#### Indicator 17 evaluation

Description	Value
ICT USE WATER UTILITIES	

Where to get the data:

Data needs to be researched locally.

Comment: This indicator should be assessed by an expert.

## Indicator 17 - ICT USE WATER UTILITIES – direct links

Water	
Waste	no direct links identified
Energy	The ICT use by water utilities can help them in achieving an optimized management with potential saving in energy consumption
Transport	no direct links identified
ІСТ	

## 3.4 Indicator 18 - ICT USE ENERGY UTILITIES

<u>Principal:</u> A measure of ICT implementation at the city utility level. A lower indicator score is given where there are less ICT tools implemented.

How to calculate:

Description	Score (0-10) evaluated locally	Comments
Operation		e.g. SCADA system, energy management
Maintenance		e.g. asset management data base and GIS
Planning and design		e.g. optimisation, GIS interface
Customer service		e.g. smart metering

For Anycity :

• 5500 homes with smart meters for gas and electricity installed. All 123,000 houses offered a smart meter by 2020.

Therefore in Anycity :

Description	Score (0-10)	Comments
Operation	10	e.g. SCADA system, energy management
Maintenance	10	e.g. asset management data base and GIS
Planning and design	9	e.g. optimisation, GIS interface
Customer service	6	e.g. smart metering

Indicator 18 = (10 + 10 + 9 + 6)/4 = 8.6

## Indicator 18 evaluation

Description	Value
ICT USE ENERGY UTILITIES	

## Where to get the data:

Data needs to be researched locally.

Comment: This indicator should be assessed by an expert.

#### Indicator 18 - ICT USE ENERGY UTILITIES – direct links

Water	no direct links identified
Waste	no direct links identified
Energy	
Transport	no direct links identified
ІСТ	

## 3.5 Indicator 19 - ICT USE TRANSPORT

Principal: A measure of ICT implementation at the city utility level. A lower indicator score is given where there are less ICT tools implemented.

How to calculate:

Description	Score (0-10) evaluated locally	Comments
Operation		e.g. coverage of installation of road sensing terminals and traffic control in the city
Maintenance		e.g. is there ICT system for planning the road maintenance and public transport vehicles?
Planning and design		e.g. is there ICT system for planning transport infrastructure expansion and improvement?
Customer service		e.g. mobile bus tickets, online feedback forms

For Anycity :

Description	Score (0-10) evaluated locally	Comments
Operation	4	e.g. coverage of installation of road sensing terminals and traffic control in the city
Maintenance	4	e.g. is there ICT system for planning the road maintenance and public transport vehicles?
Planning and design	4	e.g. is there ICT system for planning transport infrastructure expansion and improvement?
Customer service	7	e.g. mobile bus tickets, online feedback forms

Indicator 19 = (4 + 4 + 4 + 7)/4 = 4.8

## Indicator 19 evaluation

Description	Value
ICT USE TRANSPORT	

## Where to get the data:

Data needs to be researched locally.

Comment: This indicator should be assessed by an expert.

#### Indicator 19 - ICT USE TRANSPORT – direct links

Water	no direct links identified
Waste	no direct links identified
Energy	The use of ICT in transport management can help reducing travel times and energy consumption
Transport	
ІСТ	

## 3.6 Indicator 20 - ICT USE WASTE MANAGEMENT

<u>Principal:</u> A measure of ICT implementation at the city utility level. A lower indicator score is given where there are less ICT tools implemented.

How to calculate:

Description	Score (0-10) evaluated locally	Comments
Operation		e.g. ICT system for logistics of waste collection
Maintenance		e.g. is there ICT system for the pro-active maintenance of waste collection infrastruc- ture?
Planning and design		e.g. is there ICT system for planning future en- hancements and improvement of waste infras- tructure?
Customer service		e.g. smart labelling of waste bags, online feed- back forms, citizen engagement

**Example.** For Anycity :

- Waste truck management system
- Waste operation system (record how much waste is produced)
- Biffa Waste Services works with CMS SupaTrak to reduce their fuel costs and lower their vehicle carbon emissions using EcoTrak fuel saving technology that is used to identify individual driver behaviuor and trends (e.g. speed, real time MPG, green band driving)

Therefore in Anycity :

Description	Score (0-10)	Comments	
	evaluated locally		
Operation	7	e.g. ICT system for logistics of waste collection	
Maintenance	4	e.g. is there ICT system for the pro-active maintenance of waste collection infrastruc- ture?	
Planning and design	3	e.g. is there ICT system for planning future en- hancements and improvement of waste infras- tructure?	
Customer service	8	e.g. smart labelling of waste bags, online feed- back forms, citizen engagement	

Indicator 20 = (7 + 4 + 3 + 8)/4 = 5.5

## **Indicator 20 evaluation**

Description	Value
ICT USE WASTE MANAGEMENT	

Where to get the data:

Data needs to be researched locally.

Comment: This indicator should be assessed by an expert.

## Indicator 20 - ICT USE WASTE MANAGEMENT – direct links

Water	no direct links identified
Waste	
Energy	no direct links identified
Transport	no direct links identified
ІСТ	

## 3.7 Indicator 21 - DIGITAL PUBLIC SERVICE

Principal: A measure of ICT implementation within public administration (percentage of Internet users that have engaged with the public administration and exchanged filled forms online) and health system. A lower indicator score is given where there are less ICT tools implemented.

How to calculate:

Following sub-indicators need to be calculated:

• Proportion of eGovernment Users, **A**. Percentage of individuals sending filled forms over the internet to public authorities, or contacting public authorities by e-mail or website, or obtaining information from public authorities over the internet **X** divided by 10:

 $\mathbf{A}=\mathbf{X}/\mathbf{10}$ 

• Medical Data Exchange, **B**. Percentage of general practitioners using electronic networks to exchange medical data with other health care providers and professionals and to transfer prescriptions to pharmacists, **Y**, divided by 10:

 $\mathbf{B} = \mathbf{Y}/\mathbf{10}$ 

Therefore, the indicator is calculated as follows:

Indicator  $\mathbf{21} = (\mathbf{A} + \mathbf{B})/\mathbf{2}$ 

#### **Example.** For Anycity :

Percentage of individuals sending filled forms over the internet to public authorities or contacting public authorities by e-mail or website, or obtaining information from public authorities over the internet: X = 46 %. Therefore:

A = 46/10 = 4.6

Percentage of general practitioners using electronic networks to exchange medical data with other health care providers and professionals and to transfer prescriptions to pharmacists: Y = 30 %. Therefore:

B = 30/10 = 3

The indicator is calculated as follows:

Indicator 21 = (4.6 + 3)/2 = 3.8

Where to get the data:

Data needs to be researched locally.

## Indicator 21 evaluation

Description	Units	Value	Code in formula
Percentage of individuals sending filled forms over the in- ternet to public authorities, or contacting public authorities by e-mail or website, or obtaining information from public authorities over the internet	%		x
Proportion of eGovernment Users $\mathbf{A}=\mathbf{X}/10$	_		Α
Percentage of individuals sending filled forms over the in- ternet to public authorities or contacting public authorities by e-mail or website, or obtaining information from public authorities over the internet	%		Y
Medical Data Exchange ${f B}={f Y}/10$	_		В
Formula		$(\mathbf{A} + \mathbf{B})/2$	
Result			

## Indicator 21 - DIGITAL PUBLIC SERVICE – direct links

Water	no direct links identified
Waste	no direct links identified
Energy	no direct links identified
Transport	Digital public services imply a reduced number of visits of customers and citizens to public offices, with benefits in terms of traffic congestion
ICT	

## 3.8 Indicator 22 - INVESTMENT IN ICT INFRASTRUCTURE

<u>Principal:</u> A measure of the investment in the ICT infrastructure. A lower indicator score is given where the investment is lower.

How to calculate:

The infrastructure investment is an indication of the commitment to regularly invest in the ICT infrastructure. Investment can be in:

- a new infrastructure
- maintaining
- and refurbishing the existing one.

The investment in the city/region by capita, **X** is calculated as the investment in the city/region **A** divided by local population of the city/region **B**:

 $\mathbf{X}=\mathbf{A}/\mathbf{B}$ 

Subsequently, the investment in the city/region per capita X is divided by GDP per capita in the country Y.

The average lowest percentage of investment is 0.09%.

The average highest percentage of investment is 1.5%.

Therefore, the indicator is calculated as follows:

 $\label{eq:Indicator} \text{Indicator } \mathbf{22} = \frac{\mathbf{100} \times \mathbf{X}/\mathbf{Y} - \mathbf{0.09}}{\mathbf{1.5} - \mathbf{0.09}} \times \mathbf{10}$ 

**Example:** In Anycity £544 million was invested in the ICT infrastructure (in 2014/15). Population in the area is 4.533 million. Therefore the investment per capita **X** is:

 $X = 544/4.533 = 120 [\pounds/\mathrm{cap}]$ 

GDP per capita in the UK is £30074.59 [£/cap]. Therefore:

Indicator 22 =  $\frac{100 \times 120/30074.59 - 0.09}{1.5 - 0.09} \times 10 = 2.2$ 

<u>Comment:</u> the principle is the same as indicator 7 and 12.

Where to get the data:

Data for cities needs to be researched locally.

Data for countries:

http://data.worldbank.org/indicator/IE.PPI.TELE.CD/countries

## Indicator 22 evaluation

Description	Units	Value	Code in formula
Investment in the ICT infrastructure per capita (in the city/region)	£(€)/cap		x
GDP per capita (in the country)	£(€)/cap		Y
Formula		$\frac{100\times \mathrm{X/Y}-0.09}{1.5-0.09}\times 10$	
Result			

## Indicator 22 - ICT INFRASTRUCTURE INVESTMENT – direct links

Water	investment in ICT infrastructure, e.g. by refurbishing roads, may prompt water utilities to carry out necessary works
Waste	no direct links identified
Energy	investment in ICT infrastructure, e.g. by refurbishing roads, may prompt energy utilities to carry out necessary works
Transport	road works associated with investment in the ICT infrastructure may dis- turb transport
ІСТ	